

Retracta Ladder®

Retractable elevator pit ladder engineered to fit tight clearances where traditional, stationary pit ladders do not fit.



- 2¾" wall to outside of ladder when retracted for exceptionally tight car to hoistway clearance.
- 7" rung-to-wall when extended for full OSHA compliance.
- Replaces notch or pocket in the pit & hoistway wall as required for MRL elevators.
- Meets ASME A17.1/CSA B44 requirements.
- Includes Ladder Electrical Device with NC contacts positively opened mechanically.
- Traction Tread™ rungs, slip-resistant & self-cleaning for ideal multi-direction grip and strength. Full Rung Top option available.
- Gas spring reduces force required to extend or retract ladder to less than 15 lbf (< 50 lbf code).
- Pull pin with secure grip T-handle to extend & retract ladder and mechanically secure it in both positions.
- OSHA Safety Yellow powder coat painted for optimal visual safety and rust protection.
- Reversible installation – can mount Pull Pin and Ladder Electrical Device on either side.
- 4' (#RL48) thru 13' (#RL156) pit depths and 16", 12" & 9" wide rungs are standard.
- Modular design for ease of handling and reduced shipping cost.
- Works with new **Divider Beam Kit™**.
- Compliant with California Circular Letter E-10-02 for modernizations / alterations.
- **Retracta Ladder®** is a Registered Trademark and has been awarded US Patent #8944211.
- Made with pride in the USA.

Smart Elevator Tech, LLC

phone: (415) 819-5744
email: sales@smartelevatortech.com
web: www.smartelevatortech.com