

Retracta Ladder®

Retractable elevator pit ladder engineered to fit tight clearances where traditional, stationary pit ladders do not fit.



- 3" wall to outside of ladder when retracted for exceptionally tight car to hoistway clearance.
- 7" rung-to-wall when extended for full OSHA and ASME A17.1-1996 - 2013 compliance.
- Replaces notch or pocket in the pit & hoistway wall as required for MRL elevators.
- Electrical Protective Device per A17.1-2007/13, 2.26.2.38 field wired in series with elevator stop switch prevents elevator operation when ladder is extended, positive break N.C. contact, NEMA 4X (IP67) standard.
- Traction Tread™ rungs, slip-resistant & self-cleaning for ideal multi-direction grip and exceptional strength.
- Gas spring reduces force required to extend or retract ladder to less than 10 lbf (< 50 lbf code).
- Pull pin with secure grip T-handle to extend & retract ladder and mechanically secure it in both positions.
- OSHA Safety Yellow powder coat painted for optimal visual safety and rust protection.
- Reversible installation with provisions to mount micro switch & pull pin assembly on either side.
- 3' (#RL36) thru 13' (#RL156) pit depths and 16", 12" & 9" wide rungs are standard.
- Modular design for ease of handling and reduced shipping cost.
- Compliant with California Circular Letter E-10-02 for modernization & new construction.
- Retracta Ladder® is a Registered Trademark and has been awarded US Patent #8944211.
- Made with pride in the USA.

Smart Elevator Tech, LLC

phone: (415) 819-5744

email: rich@smartelevatortech.com

web: www.smartelevatortech.com

Smart Elevator Tech, LLC

Retracta Ladder® - Installation Detail

NOTE: MODEL RL48 FOR A 48" DEEP PIT SHOWN, OTHER MODELS & PIT DEPTH SIMILAR

